

功因改善/突波吸收

Power Factor Correction / Surge Absorbing

高壓電力電容器

High Voltage Power Capacitors



外型圖 / Outline Drawing




Fig.1




Fig.2

尺寸規格表 / Specification Size


突波吸收 / Surge Absorbing

1Ø / 3Ø, 50 / 60Hz

線路電壓 Line Voltage kV	容量 Capacitance (μ F) x Phase	尺寸 Size (mm)							概略重量 Weight kg	參考圖 Diagram
		A	B	C	D	E	F	S		
3.45	0.5X3	510	110	400	240	160	120	190	21.4	Fig.2
3.45	0.4X3	510	110	360	200	160	120	190	18.7	Fig.2
3.45	0.3X3	510	110	360	200	160	120	190	18.7	Fig.2
3.45	0.1X3	510	110	360	200	160	120	190	18.7	Fig.2
4.16	0.5X3	510	110	460	300	160	150	190	25.8	Fig.2
4.16	0.3X3	510	110	360	200	160	120	190	18.0	Fig.2
4.16	0.1X3	510	110	360	200	160	120	190	18.0	Fig.2
6.6	0.5X3	510	110	620	400	220	150	190	37.0	Fig.2
6.9	0.5X3	510	110	620	400	220	150	190	34.6	Fig.2
6.9	0.3X3	510	110	500	280	220	150	190	25.7	Fig.2
6.9	0.2X3	510	110	420	200	220	120	190	20.2	Fig.2
6.9	0.5X1	340	110	450	230	220	120	230	13.5	Fig.1
11	0.25X3	510	110	620	400	220	150	190	37.0	Fig.2
11.95	0.3X3	510	110	660	440	220	150	190	39.2	Fig.2
11.95	0.2X3	510	110	500	360	220	150	190	26.0	Fig.2
11.95	0.1X3	510	110	500	360	220	150	190	25.7	Fig.2
11.95	0.5X1	340	135	620	400	220	150	230	28.0	Fig.1
11.95	0.3X1	340	110	540	320	220	150	230	17.3	Fig.1
13.8	0.3X3	510	110	947	680	267	150	190	59.9	Fig.2
13.8	0.25X3	510	110	867	600	267	150	190	53.0	Fig.2
13.8	0.1X3	510	110	547	280	267	150	190	28.0	Fig.2
13.8	0.25X1	340	135	547	280	267	150	230	20.0	Fig.1
15	0.1X3	510	110	567	300	267	150	190	29.9	Fig.2
15	0.5X1	340	140	747	480	267	150	230	33.6	Fig.1
15	0.3X1	340	135	607	340	267	150	230	19.1	Fig.1
15	0.125X1	340	110	487	220	267	120	230	12.3	Fig.1
22	0.1X3	510	110	867	600	267	150	190	54.0	Fig.2
22	0.1X1	340	110	587	320	267	150	230	17.9	Fig.1
24	0.125X3	630	140	727	460	267	150	190	60.3	Fig.2
24	0.1X3	510	110	867	600	267	150	190	53.6	Fig.2
24	0.125X1	340	110	687	420	267	150	230	23.6	Fig.1
24	0.1X1	340	110	587	320	267	150	230	17.9	Fig.1
24	0.5X3	830	280	867	600	267	150	300	184	Fig.2

【其他規格規範均可承製】 Other specification available on request

外型圖 / Outline Drawing



尺寸規格表 / Specification Size

内附熔絲型 / Internal fuse type

4.16kV 3Ø 60Hz

型 式 Type	額定容量 Capacity		額定電流 Current A	尺寸 Size (mm)							接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	μF		A	B	C	D	E	F	S			
YHEA-41K100TF	100	15.33	13.9	510	110	420	260	130	150	190	M12	24	圖二 Fig.2
YHEA-41K200TF	200	30.66	27.8	510	110	610	450	130	150	190	M12	38	
YHEA-41K300TF	300	45.98	41.6	510	110	800	640	130	150	190	M12	54	
YHEA-41K400TF	400	61.31	55.5	630	135	680	520	130	150	190	M12	61	
YHEA-41K500TF	500	76.64	69.4	630	165	680	520	130	150	190	M12	76	
YHEA-41K600TF	600	91.97	83.3	630	195	698	520	133	150	190	M16	86	
YHEA-41K700TF	700	107.3	97.2	670	215	698	520	133	150	190	M16	101	
YHEA-41K800TF	800	122.6	111	750	215	698	520	133	150	190	M16	113	

内附熔絲型 / Internal fuse type

8kV 3Ø 60Hz

型 式 Type	額定容量 Capacity		額定電流 Current A	尺寸 Size (mm)							接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	μF		A	B	C	D	E	F	S			
YHEA-80K100TF	100	4.145	7.22	510	110	500	280	190	150	190	M12	28	圖二 Fig.2
YHEA-80K200TF	200	8.289	14.4	510	110	700	480	190	150	190	M12	42	
YHEA-80K300TF	300	12.43	21.7	510	110	900	680	190	150	190	M12	58	
YHEA-80K400TF	400	16.58	28.9	630	150	740	520	190	150	190	M12	71	
YHEA-80K500TF	500	20.72	36.1	630	175	740	520	190	150	190	M12	80	
YHEA-80K600TF	600	24.87	43.3	630	210	740	520	190	150	190	M12	97	
YHEA-80K700TF	700	29.01	50.5	710	215	740	520	190	150	190	M12	111	
YHEA-80K800TF	800	33.16	57.7	810	215	740	520	190	150	190	M12	126	

内附熔絲型 / Internal fuse type

11.95kV 3Ø 60Hz

型 式 Type	額定容量 Capacity		額定電流 Current A	尺寸 Size (mm)							接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	μF		A	B	C	D	E	F	S			
YHEA-119K100TF	100	1.857	4.83	510	110	490	270	190	150	190	M12	25	圖二 Fig.2
YHEA-119K200TF	200	3.715	9.66	510	110	670	450	190	150	190	M12	41	
YHEA-119K300TF	300	5.572	14.5	510	110	850	630	190	150	190	M12	57	
YHEA-119K400TF	400	7.430	19.3	630	130	740	520	190	150	190	M12	68	
YHEA-119K500TF	500	9.287	24.2	630	160	740	520	190	150	190	M12	83	
YHEA-119K600TF	600	11.14	29.0	630	185	740	520	190	150	190	M12	96	
YHEA-119K700TF	700	13.00	33.8	630	215	740	520	190	150	190	M12	111	
YHEA-119K800TF	800	14.86	38.7	730	215	740	520	190	150	190	M12	128	

【其他規格規範均可承製】 Other specification available on request

内附熔絲型 / Internal fuse type

13.8kV 3Ø 60Hz

型 式 Type	額定容量 Capacity		額定電流 Current A	尺 寸 Size (mm)							接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	μF		A	B	C	D	E	F	S			
YHEA-138K100TF	100	1.393	4.18	510	110	480	260	190	150	190	M12	26	圖二 Fig.2
YHEA-138K200TF	200	2.786	8.37	510	110	660	440	190	150	190	M12	39	
YHEA-138K300TF	300	4.179	12.6	510	110	840	620	190	150	190	M12	52	
YHEA-138K400TF	400	5.571	16.7	630	135	740	520	190	150	190	M12	64	
YHEA-138K500TF	500	6.964	20.9	630	160	740	520	190	150	190	M12	73	
YHEA-138K600TF	600	8.357	25.1	630	200	740	520	190	150	190	M12	88	
YHEA-138K700TF	700	9.750	29.3	670	215	740	520	190	150	190	M12	105	
YHEA-138K800TF	800	11.14	33.5	750	215	740	520	190	150	190	M12	117	

内附熔絲型 / Internal fuse type

23.9kV 3Ø 60Hz

型 式 Type	額定容量 Capacity		額定電流 Current A	尺 寸 Size (mm)					接線端子 Line Terminals	概略重量 Weight Kg	參考圖 Diagram
	kVAR	μF		A	B	C	D	E			
YHEA-239K100TF	100	0.464	2.42	630	140	487	220	230	20M12	32	圖二 Fig.2
YHEA-239K200TF	200	0.929	4.83	630	115	647	380	230	50M12	43	
YHEA-239K300TF	300	1.393	7.25	630	165	647	380	230	50M12	61	
YHEA-239K400TF	400	1.857	9.66	630	150	787	520	230	50M12	75	
YHEA-239K500TF	500	2.322	12.1	630	185	787	520	230	50M12	86	
YHEA-239K600TF	600	2.786	14.5	630	215	787	520	230	50M12	100	
YHEA-239K700TF	700	3.251	16.9	710	215	787	520	230	50M12	113	
YHEA-239K800TF	800	3.715	19.3	830	215	787	520	230	50M12	131	

内附熔絲型 / Internal fuse type

4.62kV 1Ø 60Hz

型 式 Type	額定容量 Capacity		額定電流 Current A	尺 寸 Size (mm)					接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	μF		A	B	C	D	E			
YHEA-46K100SF	100	12.43	21.6	340	110	560	340	190	50M12	21	圖一 Fig.1
YHEA-46K200SF	200	24.85	43.3	340	135	710	490	190	50M12	31	
YHEA-46K300SF	300	37.28	64.9	340	180	750	530	190	50M12	44	
YHEA-46K400SF	400	49.71	86.6	340	180	918	680	190	50M16	58	
YHEA-46K500SF	500	62.14	108	340	180	1078	840	190	50M16	75	

内附熔絲型 / Internal fuse type

13.8kV 1Ø 60Hz

型 式 Type	額定容量 Capacity		額定電流 Current A	尺 寸 Size (mm)					接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	μF		A	B	C	D	E			
YHEA-138K100SF	100	1.393	7.25	340	110	607	340	230	50M12	22	 圖一 Fig.1
YHEA-138K200SF	200	2.786	14.5	340	135	777	510	230	50M12	36	
YHEA-138K300SF	300	4.179	21.7	340	180	807	540	230	50M12	48	
YHEA-138K400SF	400	5.571	29.0	340	180	957	690	230	50M12	62	
YHEA-138K500SF	500	6.964	36.2	340	180	1117	850	230	50M12	80	
YHEA-138K600SF	600	8.357	43.5	340	190	1227	960	230	50M12	91	
YHEA-138K700SF	700	9.750	50.7	340	200	1327	1060	230	50M12	105	
YHEA-138K800SF	800	11.14	58.0	340	220	1357	1090	230	50M12	119	
YHEA-138K900SF	900	12.54	65.2	340	220	1467	1200	230	50M12	131	
YHEA-138K1000SF	1000	13.93	72.5	340	220	1587	1320	230	50M12	144	

内附熔絲型 / Internal fuse type

14.7kV 1Ø 60Hz

型 式 Type	額定容量 Capacity		額定電流 Current A	尺 寸 Size (mm)					接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	μF		A	B	C	D	E			
YHEA-147K100SF	100	1.228	6.80	340	110	627	360	230	50M12	23	圖一 Fig.1
YHEA-147K200SF	200	2.455	13.6	340	135	787	520	230	50M12	37	
YHEA-147K300SF	300	3.683	20.4	340	180	837	570	230	50M12	50	
YHEA-147K400SF	400	4.910	27.2	340	180	987	720	230	50M12	64	
YHEA-147K500SF	500	6.138	34.0	340	180	1147	880	230	50M12	82	
YHEA-147K600SF	600	7.365	40.8	340	190	1267	1000	230	50M12	94	
YHEA-147K700SF	700	8.593	47.6	340	200	1387	1120	230	50M12	111	
YHEA-147K800SF	800	9.820	54.4	340	220	1297	1130	230	50M12	123	
YHEA-147K900SF	900	11.05	61.2	340	220	1527	1260	230	50M12	138	
YHEA-147K1000SF	1000	12.28	68.0	340	220	1657	1390	230	50M12	152	

尺寸規格表 / Specification Size

標準型(無熔絲) / Standard type (Fuseless)

4.16kV 3Ø 60Hz

型 式 Type	額定容量 Capacity		額定電流 Current A	尺 寸 Size (mm)							接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	μF		A	B	C	D	E	F	S			
YHEA-41K100T	100	15.33	13.9	510	110	420	260	130	150	190	M12	24	圖二 Fig.2
YHEA-41K200T	200	30.66	27.8	510	110	600	440	130	150	190	M12	37	
YHEA-41K300T	300	45.98	41.6	510	110	780	620	130	150	190	M12	52	
YHEA-41K400T	400	61.31	55.5	630	130	680	520	130	150	190	M12	58	
YHEA-41K500T	500	76.64	69.4	630	155	680	520	130	150	190	M12	71	
YHEA-41K600T	600	91.97	83.3	630	185	698	520	133	150	190	M16	81	
YHEA-41K700T	700	107.3	97.2	630	215	698	520	133	150	190	M16	94	
YHEA-41K800T	800	122.6	111	710	215	698	520	133	150	190	M16	107	

標準型(無熔絲) / Standard type (Fuseless)

8kV 3Ø 60Hz

型 式 Type	額定容量 Capacity		額定電流 Current A	尺 寸 Size (mm)							接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	μF		A	B	C	D	E	F	S			
YHEA-80K100T	100	4.415	7.22	510	110	490	270	190	150	190	M12	27	圖二 Fig.2
YHEA-80K200T	200	8.289	14.4	510	110	690	470	190	150	190	M12	41	
YHEA-80K300T	300	12.43	21.7	510	110	880	660	190	150	190	M12	56	
YHEA-80K400T	400	16.58	28.9	630	140	740	520	190	150	190	M12	66	
YHEA-80K500T	500	20.72	36.1	630	170	740	520	190	150	190	M12	78	
YHEA-80K600T	600	24.87	43.3	630	200	740	520	190	150	190	M12	88	
YHEA-80K700T	700	29.01	50.5	670	215	740	520	190	150	190	M12	105	
YHEA-80K800T	800	33.16	57.7	770	215	740	520	190	150	190	M12	120	

標準型(無熔絲) / Standard type (Fuseless)

11.95kV 3Ø 60Hz

型 式 Type	額定容量 Capacity		額定電流 Current A	尺 寸 Size (mm)							接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	μF		A	B	C	D	E	F	S			
YHEA-119K100T	100	1.857	4.83	510	110	470	250	190	150	190	M12	23	圖二 Fig.2
YHEA-119K200T	200	3.715	9.66	510	110	650	430	190	150	190	M12	38	
YHEA-119K300T	300	5.572	14.5	510	110	830	610	190	150	190	M12	54	
YHEA-119K400T	400	7.430	19.3	630	125	740	520	190	150	190	M12	61	
YHEA-119K500T	500	9.287	24.2	630	155	740	520	190	150	190	M12	75	
YHEA-119K600T	600	11.14	29.0	630	180	740	520	190	150	190	M12	86	
YHEA-119K700T	700	13.00	33.8	630	205	740	520	190	150	190	M12	98	
YHEA-119K800T	800	14.86	38.7	710	215	740	520	190	150	190	M12	115	

標準型(無熔絲) / Standard type (Fuseless)

13.8kV 3Ø 60Hz

型 式 Type	額定容量 Capacity		額定電流 Current A	尺 寸 Size (mm)							接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	μF		A	B	C	D	E	F	S			
YHEA-138K100T	100	1.393	4.18	510	110	470	250	190	150	190	M12	25	圖二 Fig.2
YHEA-138K200T	200	2.786	8.37	510	110	640	420	190	150	190	M12	37	
YHEA-138K300T	300	4.179	12.6	510	110	820	600	190	150	190	M12	51	
YHEA-138K400T	400	5.571	16.7	630	130	740	520	190	150	190	M12	61	
YHEA-138K500T	500	6.964	20.9	630	155	740	520	190	150	190	M12	72	
YHEA-138K600T	600	8.357	25.1	630	180	740	520	190	150	190	M12	82	
YHEA-138K700T	700	9.750	29.3	630	205	740	520	190	150	190	M12	90	
YHEA-138K800T	800	11.14	33.5	710	215	740	520	190	150	190	M12	111	

【其他規格規範均可承製】 Other specification available on request

型 式 Type	額定容量 Capacity		額定電流 Current A	尺 寸 Size (mm)							接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	µF		A	B	C	D	E	F	S			
YHEA-239K100T	100	0.464	2.42	630	140	487	220	237	120	250	M12	32	圖二 Fig.2
YHEA-239K200T	200	0.929	4.83	630	115	647	380	237	150	250	M12	43	
YHEA-239K300T	300	1.393	7.25	630	155	647	380	237	150	250	M12	58	
YHEA-239K400T	400	1.857	9.66	630	140	787	520	237	150	250	M12	70	
YHEA-239K500T	500	2.322	12.1	630	175	787	520	237	150	250	M12	82	
YHEA-239K600T	600	2.786	14.5	630	200	787	520	237	150	250	M12	90	
YHEA-239K700T	700	3.251	16.9	670	215	787	520	237	150	250	M12	107	
YHEA-239K800T	800	3.715	19.3	770	215	787	520	237	150	250	M12	122	

型 式 Type	額定容量 Capacity		額定電流 Current A	尺 寸 Size (mm)							接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	µF		A	B	C	D	E	F	S			
YHEA-46K100S	100	12.43	21.6	340	110	550	330	190	150	230	M12	21	圖一 Fig.1
YHEA-46K200S	200	24.85	43.3	340	135	690	470	190	150	230	M12	31	
YHEA-46K300S	300	37.28	64.9	340	180	730	510	190	150	230	M12	44	
YHEA-46K400S	400	49.71	86.6	340	180	898	660	193	150	230	M16	58	
YHEA-46K500S	500	62.14	108	340	180	1038	800	193	150	230	M16	75	

型 式 Type	額定容量 Capacity		額定電流 Current A	尺 寸 Size (mm)							接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	µF		A	B	C	D	E	F	S			
YHEA-138K100S	100	1.393	7.25	340	110	597	330	237	150	230	M12	22	圖一 Fig.1
YHEA-138K200S	200	2.786	14.5	340	135	767	500	237	150	230	M12	35	
YHEA-138K300S	300	4.179	21.7	340	180	787	520	237	150	230	M12	46	
YHEA-138K400S	400	5.571	29.0	340	180	927	660	237	150	230	M12	59	
YHEA-138K500S	500	6.964	36.2	340	180	1087	820	237	150	230	M12	77	
YHEA-138K600S	600	8.357	43.5	340	190	1187	920	237	150	230	M12	87	
YHEA-138K700S	700	9.750	50.7	340	200	1287	1020	237	150	230	M12	101	
YHEA-138K800S	800	11.14	58.0	340	220	1307	1040	237	150	230	M12	114	
YHEA-138K900S	900	12.54	65.2	340	220	1417	1150	237	150	230	M12	126	
YHEA-138K1000S	1000	13.93	72.5	340	220	1527	1260	237	150	230	M12	138	

型 式 Type	額定容量 Capacity		額定電流 Current A	尺 寸 Size (mm)							接線端子 Line Terminals	概略重量 Weight kg	參考圖 Diagram
	kVAR	µF		A	B	C	D	E	F	S			
YHEA-147K100S	100	1.228	6.80	340	110	617	350	237	150	230	M12	23	圖一 Fig.1
YHEA-147K200S	200	2.455	13.6	340	135	767	500	237	150	230	M12	35	
YHEA-147K300S	300	3.683	20.4	340	180	807	540	237	150	230	M12	48	
YHEA-147K400S	400	4.910	27.2	340	180	957	690	237	150	230	M12	62	
YHEA-147K500S	500	6.138	34.0	340	180	1107	840	237	150	230	M12	79	
YHEA-147K600S	600	7.365	40.8	340	190	1227	960	237	150	230	M12	91	
YHEA-147K700S	700	8.593	47.6	340	200	1327	1060	237	150	230	M12	105	
YHEA-147K800S	800	9.820	54.4	340	220	1347	1080	237	150	230	M12	118	
YHEA-147K900S	900	11.05	61.2	340	220	1467	1200	237	150	230	M12	131	
YHEA-147K1000S	1000	12.28	68.0	340	220	1587	1320	237	150	230	M12	144	

規範及特性 / Specification and Performance

型 式 Type	高壓電力電容器 Power Capacitoors	突波吸收電容器 Surge Absorbing
依據標準 Standards	IEC 60871; CNS 1372, 3739; JIS C 4902	JEM 1362, IEC 60871, CNS 1372
產品認證 Quality approval	正字標記認證 (台正字第2846號) CNS mark (No. 2846)	Exemptions
工廠認證 Factory approval	ISO 9001(2015年版) 認證，TAF ISO 17025(2017年版)測試實驗室認證 ISO 9001:2015 certificated，TAF ISO 17025:2017 Testing Laboratory Certificated	
絕緣油 Insulation oil	非PCB絕緣油 Non-PCB fluid	
頻率 Frequency	60Hz (50Hz available on request.)	50/60Hz通用 Common use for 50 and 60Hz
容量誤差 Tolerance	-5% / +10%(三相相間容量誤差在3%以內) -5%~+10%(The capacitance tolerance between three phases is within 3%)	-5%~+10% (三相相間容量最大值與最小值比<1.08) -5%~+10% (In three-phase units, the ratio of maximum to minimum value of capacitance measured between any two terminals <1.08)
周圍溫度 Ambient temperature	-25°C / A [+40°C] ,mean 30°C / day, mean 20°C / year -25°C / B [+45°C] ,mean 35°C / day, mean 25°C / year -25°C / C [+50°C] ,mean 40°C / day, mean 30°C / year -25°C / D [+55°C] ,mean 45°C / day, mean 35°C / year	-20°C~+50°C (24小時平均溫度小於45°C) [其他溫度種類可訂製] -20°C~+50°C (24hours average below 45°C) [Other ambient temperature categories on request]
最大容許過電壓 Maximum permissible voltage	額定電壓110% (24小時平均值下) 110% of rated voltage (average voltage in every 24 hrs) 額定電壓115% (24小時中30分鐘以內) 115% of rated voltage (30 min in every 24 hrs) 額定電壓120% (5分鐘最多200次) 120% of rated voltage (5 min / max. 200times) 額定電壓130% (1分鐘最多200次) 130% of rated voltage (1 min / max. 200times)	額定電壓110% (24小時平均值下) 110% of rated voltage (average voltage in every 24 hrs) 額定電壓115% (24小時中30分鐘以內) 115% of rated voltage (30 min in every 24 hrs) 額定電壓120% (5分鐘以內) 120% of rated voltage (within 5 min) 額定電壓130% (1分鐘以內) 130% of rated voltage (within 1 min) 額定電壓182% (2秒鐘以內) 182% of rated voltage (within 2 sec) (大於115%額定電壓，在電容器壽命中不得超過200次) (The having value higher than 115% of rated voltage do not occur more than 200 times in the capacitor's life.)
最大容許過電流 Maximum permissible current	額定電流135% 135% of rated current	
損失率 Dissipation factor	小於0.05% 或 0.5W / kVAR Less than 0.05% or 0.5W / kVAR	小於0.5% Less than 0.5%
溫升 Temperature rise	周溫低於35°C時，溫升25°C以下 below 25°C at ambient temperature 35°C.	
密閉性 Sealing	80°C恆溫槽中4小時加熱，電容器外表無漏油痕跡 No oil leaking after heating at 80°C for 4hrs.	
絕緣電阻(T-C) Insulation resistance	1000MΩ以上 (端子對外殼) above 1000MΩ(Terminals to case)	
內部等效電感值 ESL (T-T)	Exemptions	2uH以下 Less than 2uH
放電特性 Discharge character	內裝放電電阻， 電容器切離電源5分鐘後其殘留電壓降至50V以下 With built-in discharge resistor, residual voltage drops to lower than 50V after capacitor is disconnected from power for 5 minutes.	無設計 Exemptions
串聯電阻 Series resistor	無設計 Exemptions	串聯電阻規格依製造者 Series resistor, the specification is according manufacturer.
端子間耐電壓 Test voltage between terminals	額定電壓×2VAC，施加10秒 Rated voltage x 2 Vac, 10 second.	3.3 / 3.45 kVAC @ 16 kVAC(1 minute) 4.16 kVAC @ 18 kVAC(1 minute) 6.0 / 6.6 / 6.9 kVAC @ 22 kVAC(1 minute) 11 / 11.95 kVAC @ 28 kVAC(1 minute) 13.8 kVAC @ 33.5 kVAC(1 minute) 15 kVAC @ 35 kVAC(1 minute) 22 kVAC @ 50 kVAC(1 minute) 24 kVAC @ 54 kVAC(1 minute)
端子與外殼間耐電壓 Test voltage between terminals and case	依額定電壓不同，試驗值依標準規定值實施 Depend on rated voltage, test value is according to the requirements of standards.	Exemptions
衝擊電壓(BIL) Impulse voltage (BIL)	依額定電壓不同，試驗值依標準規定值實施 Depend on rated voltage, test value is according to the requirements of standards.	Exemptions

【其他規格規範均可承製】 Other specification available on request



HIGH VOLTAGE POWER CAPACITORS OIL TYPE

純淨電力來自裕昌電容



裕昌機電工廠股份有限公司
YUHCHANG ELECTRIC CO., LTD.

YCE CAT-28 V03. 2024.04

總公司：台中市清水區中正街59號
台北聯絡處：台北市復興南路一段321號二樓
高雄聯絡處：高雄市復興一路5之1號

TEL : (04)2622-4188 FAX : (04)2622-4646
TEL : (02)2702-1616 FAX : (02)2706-6162
TEL : (07)241-7766 FAX : (07)291-5282

ADD: No.59, Chung Cheng St., Ching Shui Dist., Taichung City 43653, Taiwan. WEB: www.capacitor.com.tw E-mail: yce919@ms1.hinet.net